

# **UNIGUARD "HBG"** HORIZONTAL BELT GUARD **SIZING CHART**

See www.uniguardmgc.com/resources/ "Consideration Recommendation" for additional information and options.







Height should equal = shaft centerline + 1/2 sheave dia. + 2.0" clearance

### HORIZONTAL BELT GUARD NOTES

- All custom guards require a completed sizing chart
- Allow a minimum 1/4" clearance around shafts + key, shaft holes are actual sizes
- Allow a minimum 2.0" radial clearance around rotating sheaves
- Typical +/- 1.5" shaft motor adjustment equals a 3.0" shaft slot plus shaft hole size
- · Yellow material is available upon request

**Uniquard Machine Guards** 

1115 Pleasant Ridge Rd.

Greensboro, N.C. 27409

sales@uniguardmgc.com

1-888-549-4622

- · Orange is the preferred OSHA color for guarding
- Sheaves will need to be removed when "shaft holes" are chosen

SHEAVE DIA SHAFT HOLE SHAFT CENTERLINE MOUNTING FLANGE

**CHOOSE ADDITIONAL OPTIONS** 

Slotted front panel

Slotted top width panel

Slotted side width panel

Removable front panel

**FULL BOTTOM OPTIONS** 

Taper to lower shaft

Lifting handles

☐ 1/4" HDPF

☐ 9/16" HDPE

## SLOTTED FRONT PANEL REMOVABLE FRONT PANEL (Optional) (Optional) MOTOR ADJ. MOTOR ADJ. SHEAVE DIA (+/-) CHECK BOX FOR MOTOR SHAFT HOLE ADJUSTMENT SHAFT CENTERLINE FRONT VIEW (1.25" TYP.) SHAFT CENTERS Shaft centerline height measurement 1/2 SHEAVE DIA. + 2" CLEARANCE + MOTOR ADJ. excludes FULL BOTTOM material. FRONT VIEW LENGTH

I + 2 875"

(1.25" Brackets when length is <=48" as shown, else 2.0")

Length should equal = (drive + driven sheave) / 2 + shaft centers + motor adi. + 4.0" clearance

Qty.

Equip #s:

Equip #s:

Equip #s:

Notes:

**CHOOSE INSPECTION WINDOW:** 

Top center width

Front belt center (1)

Top hats are used for

Shaft centers (2)

through shafts.

**SHAFT SPACERS:** 

Driver span length

Driven span length

Driver top hat inside depth

Driven top hat inside depth

### **READ ALL NOTES PRIOR TO SUBMITTAL**

GUARD ine Guards	Uniguard Customer Name:		End User Company:	Eq. Mfg.:
	Uniguard Contact Name:		End User Contact Name:	Model:
	Phone #:	Date:	Notes:	Notes:
	E-mail:		UNI-PART#	Notes: