UNIGUARD "MBG" MOUNTED BELT GUARD **SIZING CHART**

See www.uniguardmgc.com/resources/ "Consideration Recommendation" for additional information and options.

CHOOSE ADDITIONAL OPTIONS CHOOSE INSPECTION WINDOW: OPTIONS Center width (2) ☐ Equipment Number ID Slotted front panel Slotted width panel Front belt center (1) ☐ Field modify during installation Shaft centers (2) CHOOSE ONE HOLE STYLE Removable front panel ☐ No shaft holes (any style back)☐ Shaft holes Lifting handles Top hats are used for

through shafts.

Driven span length Driver top hat inside depth Driven top hat inside depth

SHAFT SPACERS:

Driver span length


FLANGE BACK OPTIONS

☐ 1/4" HDPF Solid Flanged Back (9/16" Std) 9/16" HDPE

MOUNTING ORIENTATION


CHOOSE ONE BACK STYLE







☐ Center Split (Standard)

☐ Center Split Flanged Back





Date:



MOUNTED BELT GUARD NOTES

- All custom guards require a completed sizing chart
- Allow a minimum 1/4" clearance around shafts + key, shaft holes are actual sizes
- Allow a minimum 2.0" radial clearance around rotating sheaves
- Typical +/- 1.5" shaft motor adjustment equals a 3.0" shaft slot plus shaft hole size

Uniquard Customer Name:

Uniquard Contact Name:

- · Yellow material is available upon request
- · Orange is the preferred OSHA color for guarding
- Sheaves will need to be removed when "shaft holes" are chosen

Phone #

E-mail:

NOTES PRIOR TO SURMITTAL

LE NOTES FRIOR TO SUBMITTAL			
	End User Company:	Eq. Mfg.:	Qty.
	End User Contact Name:	Model:	Equip #s:
	Notes:	Notes:	Equip #s:
	UNI-PART#	Notes:	Equip #s:

Notes:

Uniquard Machine Guards 1115 Pleasant Ridge Rd. Greensboro, N.C. 27409

1-888-549-4622 sales@uniguardmgc.com